

855-14209

Article Number: 855-14209



Description: Connector, Fiber Optic LC Multimode OM3 (50/125), Pre-Polished (Cleave & Insert)

Base Data	Local Order Number	PFCLC10G
	Type	PFCLC
	Color	Aqua (AE)
	Features and benefits	<ul style="list-style-type: none"> • Factory-polished zirconia ceramic ferrules for quick and reliable field installations. • Unique wedge clip retains connector shape for precision connection. • Easy to use- no epoxy, heat curing, polishing or special tools required. • Color coded for easy identification. • Meet ANSI/TIA/EIA 568-B standards. • Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.
	Quantity Per	bag
	Product Description	Pre-polished connectors provide high performance and eliminate the need for the time consuming task of hand polishing ferrules in the field. A factory pre-cleaved fiber stub and index-matching gel combine to offer an immediate low loss termination of single mode or multimode fiber.
	Technical Description	Pre-Polished LC 10G 50/125 Multimode Fiber Connector, Aqua
	Short Description	Connector, Fiber Optic LC Multimode OM3 (50/125), Pre-Polished (Cleave & Insert)
	Product Dimensions	
	Port count	2
Logistic and Packaging		
	Package Quantity (Imperial)	1
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	8536700000

